



PROACTIV®



SPEEDY A1

ROBUST, VERSATILE,
JUST AS YOU NEED IT.

The **SPEEDY A1** is the multi-tool among rigid frame wheelchairs. The extremely robust frame offers you maximum stability and can be equipped with a variety of options, accessories and special constructions. The wheelchair can be ideally adapted and converted for persons weighing up to 300 kg or for persons that are 2 m tall or more.



#MoreMobility

Adaptive bikes and powerful traction devices can be connected in just a few steps via adapters.



#Reliability

The SPEEDY A1 impresses with its frame, which is designed for extreme loads and is compatible with various additional drives and adaptations.



#Flexibility

Several settings can also be made at a later time: The tipping point, seat heights or seat angle and back angle can be adapted to your needs.



#Independence

Thanks to the foldable backrest and tool-free removal of assemblies, the SPEEDY A1 is easy to transport.



PERFECT ADAPTATION. MAXIMUM RELIABILITY.

Your **SPEEDY A1** is manufactured exactly according to your requests. You determine the frame dimensions and choose from a variety of options - from footrests to brakes and push handles to seat and back systems and wheels. Your wheelchair, just like you need it.


UNIQUE, SELECTABLE OPTIONS FROM PRO ACTIV:



The 7-way angle-adjustable and foldable backrest offers maximum flexibility for the ideal sitting position.



The footrest, which can be folded towards the back with a spring locking mechanism, is easy to handle and flexible in everyday life.



Manoeuvrable one-hand drive with double handrim for users with hemiplegia or restricted mobility on one side of the body.






With our heavy duty equipment, your **SPEEDY A1** is designed for extreme loads, such as a user weighing up to 300 kg.

TECHNICAL SPECIFICATIONS

Seat width:	30 - 50 cm (in 1 cm steps)
Seat depth:	36 - 48 cm (in 1 cm steps)
Back height:	20 - 48 cm (in 1 cm steps)
Lower leg length:	33 - 52 cm (in 1 cm steps)
Rear seat height:	37 - 45 cm (in 1 cm steps)
Front seat height:	44 - 54 cm (in 1 cm steps)
Tipping point:	4 - 13 cm (in 1 cm steps)
Total product weight:	Starting at 9.9 kg
Max. standard load weight:	Up to 120 kg
Max. load weight for Heavy Duty:	Up to 300 kg appropriate individual dimensions upon request

Data subject to design changes.

FOLLOW US ON SOCIAL MEDIA



PRO^oACTIV[®]

PRO ACTIV Reha-Technik GmbH

Im Hofstätt 11
72359 Dotternhausen
info@proactiv-gmbh.de

www.proactiv-gmbh.com

Rev. 11/2025_01

Subject to technical modifications, printing errors & colour deviations.